

Low-profile Hand Pallet Truck **SAC51**

- ◆ SAC low-profile manual hydraulic pallet truck is suitable for pallet that is less than 51mm above the ground and space is narrow.
- ◆ At the same time ,it has all the characteristics of ordinary hydraulic trucks.



Model	SAC51 Low-profile
Capacity	2000kg
Pump	AC integrated pump
Wheel	PU/RU/Nylon
Steering Wheel Size	180×50 Nylon/PU/RU/Rubber
Single Loading Wheel Size	Nylon/PU wheel 85×93
Double Loading Wheel Size	Nylon/PU wheel 50×70
Lift	105mm
Max. Lifting Height	156mm
Min. Lifting Height	51mm
Width of Outer Fork	540/685mm
Length of Fork	1150/1220mm
Steel Thickness after Painting	3mm
Ribbing	No tendons
Handle	Rubber packaged handle



Hand Pallet Truck **BF** series

- ◆ Rubber coated handle comfortable even under extreme temperature conditions.
- ◆ Fully sealed hydraulic unit housing.
- ◆ Single valve cartridge for easy maintenance.
- ◆ Powder coated chassis made of high grade steel.
- ◆ Conforms to EN1757-2.

Model	BF20	BF25	BF30
Capacity (kg)	2000	2500	3000
Max. Fork Height (mm)	200 or 190		
Min. Fork Height (mm)	85 or 75		
Fork Length (mm)	1150/1220		
Fork Overall Width (mm)	550/685		
Fork Width (mm)	160		
Front Wheel (mm)	Ø80×70 or Ø74×70, Nylon, Polyurethane		
Steer Wheel (mm)	Ø200 or Ø180×50 Nylon, Polyurethane, Rubber		
Net Weight (kg)	75	78	78



Hand Pallet Truck **HM** series

One of best selling in the world.

- ◆ A built in overload valve and totally sealed hydraulic pump.
- ◆ German seal kit offers long span life of pump for 3 years warranty.
- ◆ Heavy duty and reinforced forks for greatest strength and durability.
- ◆ Guide rollers offer easier entry and exit.
- ◆ Maintenance free oilless bushings at key points offer you less operating force and longer life span.
- ◆ Conforms to EN1757-2.



Option-Support wheels



Option-Support wheels

Model	HM6	HM7F (The casting pump is most popular in the market)
Capacity (kg)	2500	2500
Max. Fork Height (mm)	75	80
Min. Fork Height (mm)	190	190
Max. Lifting Height (mm)	≥110	≥110
Fork Outside Distance (mm)	680	550/680
Fork Length (mm)	1200	1150/1200
Fork Size (mm)	150×50	150×50
Load Double Wheel (mm)	Ø72×70	Ø72×70
Steering Wheel (mm)	Ø180×50	Ø180×50
Material of Wheel	Nylon/PU	Nylon/PU
Type / Size	680×1200mm(27"×48")	550×1150 / 680×1200 / 2.5T(Paid optional 3T)
Pump	OPK Welding Pump,DF Pump,AC Pump	Casting Pump
Packing	1.6pcs/pallet,680-144pcs/1×20" container 2.6pcs/pallet,680-324pcs/1×20" container	1.6pcs/pallet,550--180pcs/680-144pcs/1×20" container 2.6pcs/pallet,550--378pcs/680-324pcs/1×20" container