

## Mini Electric Pallet Truck **CEY20WE**

- ◆ Capacity:1500kg, DC power, light-duty conditions.
- ◆ Fit for small work space, double-side pallet can use.
- ◆ Maintenance-free battery/easy replance/inner charger.
- ◆ Replace hand pallet truck, load/unload on vehicles.
- ◆ Low voltage protection, truck will stop if voltage is lower, make truck/battery with long using life.
- ◆ Emergency stop/hour meter/Battery level indicator.



Model		CEY20WE
Load Capacity	(kg)	2000
Load Center	(mm)	600
Wheel Base	(mm)	1390
Operating Type		Walkie
Wheels Type		PU
Wheel quantity Driving Wheel / Balance Wheel / Bearing Wheel		1/1/4
Driving Wheel Size	(mm)	Ø248×75
Balance Wheel Size	(mm)	Ø80×80
Bearing Wheel Size	(mm)	Ø115×55
Min. Fork Lowered Height	(mm)	85
Max. Fork Lifting Height	(mm)	195
Max. Lifting Height	(mm)	110
Overall Fork Width	(mm)	540/600/685
Fork Length	(mm)	1150/1200
Fork Width	(mm)	185
Fork Thickness	(mm)	55
Overall Length	(mm)	1750
Overall Width	(mm)	720
Overall Height(With Handle)	(mm)	1385
Overall Height(Without Handle)	(mm)	850
Min. Turning Radius	(mm)	1575
Min. Aisle Width for Pallets 800×1200	(mm)	1900
Min. Aisle Width for Pallets 1000×1200	(mm)	1940
Travelling Speed (laden / unladen)	(km/h)	4/4
Lifting Speed (laden / unladen)	(mm/s)	56/60
Lowering Speed (laden / unladen)	(mm/s)	57/59
Gradeability (laden / unladen)	(%)	5/7
Driving Motor	(KW)	AC 1.5
Lifting Motor	(KW)	DC 2.0
Steering Motor	(KW)	DC 0.15
Battery Voltage / Capacity	(V/Ah)	24/210
Brake		Electromagnetic / Regenerative
Controller		CURTIS 1230
Battery Weight	(kg)	190
Service Weight with Battery	(kg)	600

## Walkie Electric Pallet Truck **CEY18/20W**

- ◆ Ddouble-side pallet can be used.
- ◆ AC free maintenance motor, without carbon brush.
- ◆ Small turning radius, fit for narrow space.
- ◆ Electric lifting, rapid, efficient, limited switch.
- ◆ Outsider charger.
- ◆ Low voltage protection, truck will stop if voltage is lower, make truck/battery with long using life.
- ◆ Emergency stop/hour meter/Battery level indicator.



Model		CEY18/20W
Load Capacity	(kg)	1800/2000
Load Center	(mm)	600
Wheel Base	(mm)	1300
Operating Type		Walkie
Wheels Type		PU
Wheel Quantity Driving Wheel / Balance Wheel / Bearing Wheel		1/1/4
Driving Wheel Size	(mm)	Ø228×75
Balance Wheel Size	(mm)	Ø84×80(Double wheels)
Bearing Wheel Size	(mm)	Ø115×55
Min. Fork Lowered Height	(mm)	85
Max. Fork Lifting Height	(mm)	195
Max. Lifting Height	(mm)	100
Overall Fork Width	(mm)	550/600/650/685
Fork Length	(mm)	1150/1200
Fork Width	(mm)	170
Overall Length	(mm)	1650
Overall Width	(mm)	725
Overall Height(With handle)	(mm)	1380
Overall Height(Without handle)	(mm)	890
Min. Turning Radius	(mm)	1450
Min. Aisle Width for Pallets 800×1200	(mm)	1866
Min. Aisle Width for Pallets 1000×1200	(mm)	1921
Travelling Speed (laden / unladen)	(km/h)	3.5/4.0
Lifting Speed (laden / unladen)	(mm/s)	20/25
Lowering Speed (laden / unladen)	(mm/s)	40/30
Gradeability (laden / unladen)	(%)	5/7
Driving Motor	(KW)	AC 0.95
Lifting Motor	(KW)	DC1.2
Steering Motor	(KW)	-
Battery Voltage / Capacity	(V/Ah)	24/210
Brake		Electromagnetic / Regenerative
Controller		CURTIS
Battery Weight	(kg)	202
Service Weight with Battery	(kg)	552