

## Side Tiller Electric Stacker **CH15** series

- ◆ WINNER hydraulic power pack, low noise, few vibration and excellent leak tightness, ensures smooth lifting.
- ◆ High-strength frame design and "C" shaped mast, strong and durable, ensures longer service life.
- ◆ Tiller in side, makes the operator has wide visible range.
- ◆ CH Series configure with 100Ah battery, intelligent built-in charger.
- ◆ REMA plug from Germany.



CH15

Model	CH15-25	CH15-31	CH15-33
Load Capacity	(kg)	1500	
Load Center	(mm)	600	
Overall Length	(mm)	1892	
Overall Width	(mm)	840	
Overall Height	(mm)	1825	2225
Lifting Height	(mm)	2500	3100
Max. Working Height	(mm)	3144	3630
Lowered Fork Height	(mm)		90
Fork Dimension	(mm)	1150×160×56	
Max. Fork Width	(mm)	540/680	
Min. Aisle for Stacking	(mm)	2280	
Turning Radius	(mm)	1475	
Driving Motor	(Kw)	0.75	
Lifting Motor	(Kw)	2.0	
Battery	(V/Ah)	24/100	
Battery Weight	(kg)	45	
Net Weight(without Battery)	(kg)	560	593
			603

## Stacker **CDY15D**

Capacity:1500kg,Lifting Height:2000-3300mm,Straddle leg as option.

- ◆ Separately excited motor,strong climbing ability.
- ◆ High strength forks.
- ◆ Built-in charger.
- ◆ Automatic lifting limit,motor and battery life extension.
- ◆ Stepless speed control system,safe and quite.
- ◆ Controller with multiple automatic protection.
- ◆ Emergency reversing device.



Model	CDY15D
Mast Type	2-Stage STD
Load Capacity	(kg) 1500
Load Center	(mm) 600
Wheel Base	(mm) 1166
Operating Type	Walkie
Wheels Type	PU
Standard Lift Height	(mm) 2000/2500/3000/3300
Max. Extend Height	(mm) 2515/3015/3515/3815
Mast Lowered Height	(mm) 1560/1810/2060/2210
Lowered Fork Height	(mm) 90
Fork size (Length/Width/Thickness)	(mm) 1150(1220)/185/55
Overall Length	(mm) 1764
Overall Width	(mm) 790
Outside Width between Forks	(mm) 550/600/650/685
Inside Width between Forks	(mm) 180/230/280/315
Min. Turning Radius	(mm) 1365
Min. Aisle Width for Pallets 800×1200	(mm) 1970
Min. Aisle Width for Pallets 1000×1200	(mm) 1930
Min. Ground Clearance	(mm) 30
Travelling Speed (laden / unladen)	(km/h) 3/3.5
Lifting Speed (laden / unladen)	(mm/s) 100/180
Lowering Speed (laden / unladen)	(mm/s) 120/120
Gradeability (laden / unladen)	(%) 5/7
Drive Motor / Lift Motor	(kw) DC0.63/DC2.2
Battery Voltage	(V) 24
Battery Capacity	(Ah) 85
Brake	Electromagnetic / Regenerative
Battery Weight	(kg) 52
Service Weight with Battery	(kg) 760