

Adjustable Work Positioners **XL series**

- ◆ Reduces ergonomic strain-positions your work at the precise height and angle you select.
- ◆ Choose table height range 510-700mm or 720-1070mm great for dies, mould, parts bin, etc.
- ◆ Lightweight, mobile, all-steel construction.
- ◆ Platform can be set at various heights and tilted to a certain angle to reduce strain and overexertion.
- ◆ Telescoping shaft with safety lever secures the work positioners to the height you want.
- ◆ Four swivel casters making the work positioners extremely easy to maneuver.
- ◆ Angle of table is adjustable from 0-40°.
- ◆ A valve core for pneumatic purpose.



Model	XL15A	XL15B	XL15C
Capacity (kg)	150	50	150
Table Height Range (mm)	510-700	720-1070	720-970
Adjustable Table Angle	0-40°	0-40°	0°
Net Weight (kg)	28	30	23

Hydraulic Work Positioner **XH series**

- ◆ Reduces ergonomic strain-positions your work at the precise height and angle you select.
- ◆ Table height 720-1070mm great for dies, mould, parts bin, etc.
- ◆ Lightweight, mobile, all-steel construction.
- ◆ Platform can be set at various heights and tilted to a certain angle to reduce strain and overexertion.
- ◆ Hydraulic pump lift the platform to the height you want.
- ◆ Four swivel casters making the work positioners extremely easy to maneuver.



Model	XH15A	XH20
Capacity (kg)	150	200
Table Height Range (mm)	720-1070	720-1070
Adjustable Table Angle	0-40°	0-40°
Net Weight (kg)	38	38

Carousel Pallet Turn **CPT series**



Model	CPT10-1	CPT10-2	CPT10-3	CPT20-1	CPT20-2	CPT30-1
Capacity (kg)		1000			2000	3000
Top Inside Dia. (mm/inch)	Ø673/28.5	Ø825/32.5	Ø915/36	Ø915/36	Ø1130/44.5	Ø927/36.5
Top Outside Dia. (mm/inch)	Ø762/30	Ø915/36	Ø1016/40	Ø1016/40	Ø1220/48	Ø1016/40

All-Around Airbag Automatic Load Leveler **SP4500** Airbag Palletizer - Pallet Positioner

- ◆ Load and unload pallets without stooping, stretching, or walking.
- ◆ The P3-All Around Pneumatic Load Leveler automatically maintains pallets at a constant level and comfortable working height as layers of boxes are added or removed.
- ◆ Leveling is accomplished by a heavy-duty, reinforced rubber airbag that can handle loads up to 4500 lbs.
- ◆ After airbag charging with shop air is complete, the P3 All Around can be disconnected and moved to any location in the plant. Because the P3 is pneumatic, it can accommodate loads that vary substantially in weight (from 400 - 4500 lbs.) so one unit is versatile enough to work in several areas.



Model	SP4500
Load Capacity (kg)	2050
Raised Height (mm)	705
Lowered Height (mm)	241
Overall Base (WxL) (mm)	910x910
Turntable Dia. (mm)	Ø1105
Shipping Weight (kg)	182