## Pallet Sping Positioner and Level Loader **SP-2000**

- Automatically maintain a load at the ideal height for manual loading and unloading.
- Automatically maintain the top of the load at the working height.

CE

- ◆ Includes a steel scissor lift mechanism and at least one large compression spring.
- ◆ The springs are chosen to match the weight and height of a fully loaded pallet.
- With a shock absorber to eliminate tendency for the load to bounce on the springs.

## Electric Rotating Lift Table **ALT-EH / ALT-EP** series

- ♦ 360 degree rotating closed platform.
- ♦ Easy to be moved by the forklift.
- Internal power pack equipped with relief valve against overloading and compensated flow valve for controlled lowering speed.
- ♦ Heavy duty cylinders with drainage system and check valve to stop the lift table lowering in case of hose burst.
- With hand controller, foot pedal controller as optional.
- ◆ Single phase power supply as optional.
- External power unit as optional.



Carousel pallet turn with brake







Stainless





Galvanized



Option-Solid Disc with Cover

Option-Skirt cover





Model		ALT1000EH	ALT2000EH	ALT1000EP	ALT2000EP
Capacity	(kg)	1000	2000	1000	2000
Operation Type	(mm)	Electric (Handle)	Electric (Handle)	Electric (Pedal)	Electric (Pedal)
Diameter of Platform	(mm)	1110	1110	1110	1110
Min. Platform Height	(mm)	300	300	300	300
Max. Platform Height	(mm)	700	700	700	700
Basement Length	(mm)	934	934	934	934
Basement Width	(mm)	922	922	922	922
Lift Time	(s)	15-20	20-25	15-20	20-25
Power Pack		380V/50HZ, AC 1.1 KW	380V/50HZ, AC 2.2KW	380V/50HZ, AC 1.1 KW	380V/50HZ, AC 2.2KW
Net Weight	(kg)	163	175	164	176

Model		SP-2000
Capacity	(kg)	200-2000
Compressed Height	(mm)	240
Extended Height	(mm)	710
Rotation Ring, Outside Dia.	(mm)	Ø1110
Rotating Ring Inside Dia.	(mm)	Ø1035
Base Frame Length	(mm)	1150
Base Frame Width	(mm)	930
With 3 springs		Large, Middle, Small
Net Weight	(kg)	128

CE

