

Double Scissor Lift Table *HD* series

- ◆ Heavy duty design.
- ◆ Meet EN1570 norm and ANSI/ASME safety standard.
- ◆ High quality power unit made in Europe.

Standard Safety Features

- ◆ Upper platform lifted with aluminum safety bar preventing descent on contact with obstructions.
- ◆ Internal power pack equipped with relief valve against overloading and compensated flow valve for controlled lowering speed.
- ◆ Heavy duty cylinders with drainage system and check valve to stop the lift table lowering in case of hose burst.
- ◆ Safety clearance between scissors to prevent trapping during operation.

Other Standard Features

- ◆ Self lubricating bushings on pivot points.
- ◆ Removable lifting eye to facilitate handling and lift table installation.



Model	HD1000	HD2000	HD4000
Capacity (kg)	1000	2000	4000
Lowered Height (mm)	305	360	400
Raised Height (mm)	1780	1780	2050
Platform Size LxW (mm)	820x1300	850x1300	1700x1200
Base Frame Size (mm)	640x1240	785x1220	1600x900
Lift Time (sec)	35~45	35~45	55~65
Power Pack	380V/50Hz, AC1.1kw	380V/50Hz, AC1.5kw	380V/50Hz, AC2.2kw
Net Weight (kg)	255	282	630

Three Scissor Lift Table *HT* series

- ◆ Heavy duty design.
- ◆ Meet EN1570 norm and ANSI/ASME safety standard.
- ◆ High quality power unit made in Europe.

Standard Safety Features

- ◆ Upper platform lifted with aluminum safety bar preventing descent on contact with obstructions.
- ◆ Internal power pack equipped with relief valve against overloading and compensated flow valve for controlled lowering speed.
- ◆ Heavy duty cylinders with drainage system and check valve to stop the lift table lowering in case of hose burst.
- ◆ Safety clearance between scissors to prevent trapping during operation.

Other Standard Features

- ◆ Self lubricating bushings on pivot points.
- ◆ Removable lifting eye to facilitate handling and lift table installation.



Model	HT1000	HT2000	HT4000	HT5000
Capacity (kg)	1000	2000	4000	5000
Lowered Height (mm)	470	560	625	890
Raised Height (mm)	3000	3000	3200	5100
Platform Size LxW (mm)	1700x1000	1700x1000	1700x1200	2980x2000
Base Frame Size (mm)	1600x1000	1606x1010	1610x1140	2980x2000
Lift Time (s)	35~45	50~60	70~80	90~105
Power Pack	380V/50Hz, AC2.2kw			380V/50Hz, AC3kw
Net Weight (kg)	433	494	910	1500