

Low Profile Lift Table **HX** series

- ◆ Concave-shaped platform with super-low height.
- ◆ With explosion-proof valve.



Model	Capacity (kg)	Platform Size LxW (mm)	Min. Height (mm)	Max. Height (mm)	Overall Size LxW (mm)	Lifting Time (s)	Power Pack (V/Hz)	Net Weight (kg)
HX500	500	1270x1100	25	800	1515x1715	25-30	380/50	320
HX750	750	1270x1100	25	800	1515x1715	25-30	380/50	370
HX1000	1000	1270x1100	35	800	1515x1715	25-30	380/50	400
HX1500	1500	1270x1100	35	800	1515x1715	25-30	380/50	470

Low Profile Lift Table **HE** series

- ◆ These tables achieve a low closed height, eliminating the need for a pit installation.
- ◆ They are manufactured to all European safety standards including EN1570:1999.
- ◆ Remote power pack with pedestal and controls IP54 protection.
- ◆ 4V control box with UP and down buttons and emergency stop.
- ◆ External power pack equipped with a relief valve against overloading and a compensated flow valve for controlling lowering speed. Power supply are AC 380V/50HZ/3phase.
- ◆ Hose burst safety valve to stop the lift table lowering in case of hose breakage.



HE1000

Model		HE500	HE1000	HE1500	HE2000
Capacity	(kg)	500	1000	1500	2000
Platform Size	LxW (mm)	1400x1200	1400x1200	1500x1300	1500x1300
Min. Height	(mm)	85	85	85	100
Max. Height	(mm)	885	885	885	820
Stroke	(mm)	800	800	800	720
Lifting Time	(s)	25-30	25-30	30-40	30-40
Power Pack		380V/50HZ, 0.75KW	380V/50HZ, 1.1KW	380V/50HZ, 2.2KW	380V/50HZ, 2.2KW
Net Weight	(kg)	207	280	380	500

Low Profile Lift Table with Automatic Stopper **HYS** series

- ◆ Heavy duty design with larger platform.
- ◆ These tables achieve a low closed height, eliminating the need for a pit installation.
- ◆ They are manufactured to all European safety standards including EN1570:1999.
- ◆ Remote power pack with pedestal and controls, protected to IP54.
- ◆ Upper platform fitted with safety perimeter to prevent descent on contact with obstructions.
- ◆ 24V control box with UP and DOWN buttons and emergency stop.
- ◆ External power pack equipped with a relief valve against overloading and a compensated flow valve for controlling lowering speed. Power supply are AC 380V/50HZ/3phase.
- ◆ Hose burst safety valve to stop the lift table lowering in case of hose breakage.
- ◆ Removable lifting eyes to facilitate handling and installation of the lift table.
- ◆ Oilless bushings on pivot points.
- ◆ Loading ramp is a standard equipment.



Stainless available
Remote wireless controller available



Wireless remote controller is available

Model	Capacity (kg)	Platform Size LxW(mm)	Min. Height (mm)	Max. Height (mm)	Stroke (mm)	Lifting Time (second)	Power Pack	Net Weight (kg)
HYS1001	1000	1450x1140	85	860	775	25	380V/50HZ, AC 0.75kw	357
HYS1002	1000	1600x1140	85	860	775	25	380V/50HZ, AC 0.75kw	364
HYS1003	1000	1450x800	85	860	775	25	380V/50HZ, AC 0.75kw	326
HYS1004	1000	1600x800	85	860	775	25	380V/50HZ, AC 0.75kw	332
HYS 0501	500	1450x1140	85	860	775	25	380V/50HZ AC 0.75kW	350