

Mobile Aluminium Work Platform **AWP** series



AWP6-1000



AWP6-2000



Model		AWP6-1000	AWP8-1000	AWP10-1000	AWP6-2000	AWP8-2000	AWP10-2000	AWP12-2000
Max. Platform Height	(mm)	6000	8000	10000	6000	8000	10000	12000
Working Height	(mm)	7700	9700	11700	7700	9700	11700	13700
Ground Clearance	(mm)	80	80	80	80	80	80	80
Lift Rated Capacity	(kg)	150	125	125	300	300	250	200
Platform Size	(mm)		650×600		1500×600	1500×600	1620×600	1740×600
Outspread Size	(mm)		1930×1770		1950×1850	1950×1850	2130×1980	2550×2500
Electrical Source	AC	(V)	220			220		
	DC	(V)	24			24		
Battery	(V/Ah)		2×12/60			2×12/60		
Charger	(V/A)		24/10			24/10		
Lifting Motor	AC	(V/Kw)	220/0.75			220/1.5		
	DC	(V/Kw)	24/1.2			24/2.2		
Overall Length	(mm)		1330		1550	1550	1670	1790
Overall Width	(mm)		800		900	900	900	900
Overall Height	(mm)	1950	2050	2150	1970	1970	2070	2070
Net Weight	AC	(kg)	300	350	400	480	580	680
	DC	(kg)	330	380	430	510	610	710

Self-Propelled Working Platform **CAWP** series



Model		CAWP75	CAWP90
Max. Platform Height	(mm)	7500	9000
Max. Machine Height	(mm)	9000	10500
Min. Platform Height	(mm)		680
Ground Clearance	(mm)		20
Lift Rated Capacity	(kg)	200	150
Platform Size	(mm)		1000×700×1100
Max. Drive Speed (Platform Stowed)	(km/h)		3-4
Max. Drive Speed (Platform Elevated)	(km/h)		0.6-1
Min. Turn Radius	(mm)		1800
Max. Climbing Capacity	(%)		20
Directional Wheel Size	(mm)		205×100
Driving Wheel Size	(mm)		305×100
Driving Motor	(V/Kw)		2×2.4/0.5
Lifting Motor	(V/Kw)		24/2.2
Battery	(V/Ah)		2×12/150
Charger	(V/A)		24/25
Pothole Protection System			Mechanical Control
Overall Length	(mm)		1700
Overall Width	(mm)		1000
Overall Height	(mm)	2080	2180
Net Weight	(kg)	1100	1250